## **Enlighted Asset Tag 1U**

# **Enlighted**

## AT-1U-H1

#### SPECIFICATION

The Enlighted Asset Tag 1U is a part of Enlighted's Real-Time Location Service (RTLS) solution. The Enlighted Asset Tag 1U transmits Bluetooth Low Energy (BLE) advertisements received by the Enlighted Sensor Network. By physically attaching the Enlighted Asset Tag to objects, the application can quickly and reliably locate and track assets.

Designed to track assets in a variety of applications and environments, the Enlighted Asset Tag 1U has an IP67 rated enclosure constructed of materials capable of withstanding medical cleaners and harsh industrial environments. With an expected battery life of five

The tag can be secured to a flat surface with an integrated adhesive strip or to a curved

advertising message ensuring only valid tags are tracked by the Enlighted Sensor Network

years in asset tracking use cases, the tag is long-lasting, reliable, and durable.

# E Enlighted

**Enlighted Asset Tag** 



Asset Tag Mounting Bracket

#### surface with a separate mounting bracket. Each tag transmits its unique ID and proprietary

and the application.

**OVERVIEW** 

#### **FEATURES**

- Broadcasts Bluetooth Low Energy (BLE) advertisements
- The integrated accelerometer detects motion and adjusts advertising rate to optimize battery life
- Easy user button activation for use with the application

#### Enlighted Asset Tag

Body	L	3"	77 mm
	W	1.3"	34 mm
	Н	0.5"	14 mm
Weight		1.76 oz	50 gms


#### **DATA PRIVACY**

The Enlighted Asset Tag 1U broadcasts BLE beacons received by Enlighted sensors to compute the location of the asset tag. The tag does not have the ability to directly reference, distinguish or identify any natural person or the asset it might be associated with.

#### **DIMENSIONS**



### MOUNTING THE TAG



Mounting the tag to a curved surface using the bracket

#### **TECHNICAL SPECIFICATIONS**

Sensor Case: Tritan™ Copolyester MX731 chemically stable, medical grade, FDA/ISO 10993, chemically


resistant acrylic adhesive

Operating Temp: -20 to 50 °C/

-4 to 140 °F

Enclosure: IP67 rating

Battery: 5 years with typical use



#### **ORDERING INFORMATION**

AT-1U-H1 Enlighted Asset Tag 1U **BRKT-AT-1U** Mounting Bracket for curved

surface

AT-CARD-MT Enlighted Badge Tag

AT-BUTTON-WBAND Enlighted Button Wristband Tag

AT-BUTTON Enlighted Beacon Tag

#### **COMPLIANCE**

 $C \in$ Europe

**United States** 

FC

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG. Inc. and any use of such marks by Enlighted Inc. is under license. Other trademarks and trade names are those of their respective owners.