# Enlighted Room Control WS-2-00



SPECIFICATION

The Enlighted Room Control (ERC) enables manual control of light fixtures through Enlighted's intelligent lighting control system.

### **OVERVIEW**

The Enlighted Room Control provides the basic control functions of a standard wall switch with preset dimming capabilities without any additional wiring. The Enlighted Room Control enables you to select preset scenes so that groups of light fixtures behave in concert to achieve a lighting objective. The Enlighted Room Control gives you the flexibility to predefine up to six different scenes and many combinations of light levels that can be accessed at the push of a button.

# AUTO

# **FEATURES AND BENEFITS**

**Localized Microprocessor Control:** Each Enlighted Room Control is a fully-fledged computing and communications device. The control communicates with Enlighted Smart Sensors wirelessly, enabling the sensor to make local decisions regardless of the network status.

**Programmable:** Scene configurations are defined for each Enlighted Room Control and are saved in the Enlighted Smart Sensor's memory during control commissioning. Scenes are easily configured and changed through the browser-accessible Manage.

**Code Compliant:** For regions where building codes require that a manual-on/auto-off switch be located in an enclosed space, the Enlighted Room Control fulfills this requirement.

**Simple and Low-cost Installation:** Designed to fit on a standard wall plate, the Enlighted Room Control can replace a standard wall switch, yet it does not require any external power or special low voltage wiring. In locations without an existing switch, the Enlighted Room Control can be installed directly on the wall or over existing junction boxes.

**Effortless Operation:** Intuitive buttons enable occupants to brighten and dim lights, as well as cycle through lighting scenes, and return to original settings. When a space has been unoccupied for a predetermined period of time, the Enlighted system reestablishes automatic control.

**Standards-Based Networking and Security:** The 802.15.4 compatible radio transmits messages in the 2.4GHz band while avoiding interference with any Wi-Fi or other networks. All messages are AES-128 encrypted to provide network security.

**Minimal Air-time:** The Enlighted Room Control transmits its messages in short bursts to Enlighted sensors, utilizing very little channel capacity and minimizing collisions with other network traffic.

**Minimal Maintenance:** With an expected battery life of more than five years, the Enlighted Room Control has minimal maintenance requirements.

# The Enlighted Room Control (ERC)

L 2.61" 66.4 mm W 1.29" 32.7 mm H .45" 11.5 mm

# **ENLIGHTED SPECIFICATION SUBMITTAL**

Job Name:	_
Job Number:	
Product Code:	
☐ WS-2-00	

# **Enlighted Room Control**





# **BRIGHT**

Tap to turn lights on Press and hold to gradually brighten

Tap to turn lights off Press and hold to gradually dim

Press for customized room scenes

Press to reset lights to original levels

# INSTRUCTIONS FOR WALL MOUNTING

- 1. Align the Enlighted Room Control within the back-plate, with top button arrow pointing up. Affix to the control by firmly tightening both captive screws.
- 2. Align spacers to the control. Place spacers against the back of the control—one at the top and one at the bottom—and align the spacers with the oval screw hole of the mounting plate. Ensure the flush side of the spacers faces the wall. Hold in place against the desired wall location.
- 3. Screw on the back-plate using tapping screws provided.
- 4. Snap on the wall plate with the arrow pointing up.

# **TECHNICAL SPECIFICATIONS**

Action: Four push buttons;

Up to six software-configurable scenes Actuations: Rated for 50,000 actuations Power: Battery-powered: CR2032

Battery Life: 5 years based on average usage

Max Fixtures Per Control: 100

Interoperability: Enlighted Sensors and Gateways

Operating Temp.: 32° to 122° F / 0° to 50° C

Enclosure: Recyclable ABS

Wireless Standards: IEEE 802.15.4 Radio Frequency: 2400-2483.5 MHz RF TX Output Power: 3.5 dBm (average)

Wireless Range: Up to 150 ft. (46 m) radius open range

Encryption: AES-128

# ORDERING INFORMATION

WS-2-00 Enlighted Room Control

# **COMPLIANCE**

Europe

CE ROHS REACH United States FC U

Canada

**WARRANTY**: 5 years

View www.enlightedinc.com/limited-warranty-terms

for complete terms and conditions